

30-MTK INSTALLATION INSTRUCTIONS

The Hustler 30-MTK modifies the 4-BTV or 5-BTV for 30 meters operations. A 30 meter trap and two shorter tubes replace the original 56" 40 meter tube. The three and six element spider assemblies are eliminated.

ASSEMBLY

If you are converting a 4-BTV it will be necessary to trim the 36" tube (part #4190-1) to 33" length. After trimming, cut two vertical slots approximately 1 1/2" long in the end of the tube to allow the clamp to operate. **DO NOT TRIM THIS TUBE IF YOU ARE CONVERTING A 5-BTV (10-80 METERS).**

Check the parts against the parts list.

Remove all sections of the antenna above the 20 meter trap. Place the 24" tube (part #4087-11) and two clamps on the 20 meter trap. Install the 30 meter trap (see illustration) and set dimension "E" to 1 1/2". Mount the 36" tube (part #4190-1) and clamp. Also install your 75/80 meter resonator if you are using a 5-BTV. Set dimension "F" (see illustration) to 1 1/2".

RADIALS

If you are using radials in your installation cut two radials, 23 1/2' in length, for 30 meters. Use #14 gauge or larger insulated wire. The radials should be placed 180 degrees opposite of each other. Try to maintain even spacing between radials.

TUNING

10, 15 and 20 meters should be unaffected. Check the V.S.W.R. on 30 meters. To lower the resonant frequency lengthen dimension "E" in 1/2" increments. To raise the resonant frequency shorten "E" in 1/2" increments. Follow the same procedure for 40 meters but adjust "F" in 1" increments. If you are using a 5-BTV check the V.S.W.R. on 75/80 meters and retune (if necessary) as normal.

GUYING

Guying is strongly recommended due to the added wind load. Use nonconductive guys tied off above the 20 meter trap.



New-Tronics Antenna Corp.
One Newtronics Place
Mineral Wells, TX 76067-9563
940-325-1386

This PDF courtesy of



30-MTK

6750

PARTS LIST

Part No.	Description	Qty.
4087-11	Aluminum Tube 1 1/4" x 24"	1
4090-4	30 Meter Trap	1
4190-1	Aluminum Tube 1 1/4" x 36"	1
3152-4	Tube Clamp	3
6099	Danger Label	1

NEW-TRONICS ANTENNA CORPORATION LIMITED WARRANTY


New-Tronics Antenna Corp. warrants its products to be free of defects in material and workmanship and extends this warranty under intended use and normal service conditions to the original owner for a period of one year from the date of purchase. This warranty does not apply to any product that has been repaired or altered in any manner and is void for any damage due to accident, neglect, unreasonable use, improper installation, or any other cause not arising out of defects in material or workmanship.

The obligations of New-Tronics Antenna Corporation are limited to repairing or replacing, at its option, any product or part that is returned to the factory; all transportation charges prepaid, accompanied by proof of purchase, and upon examination reveals to have been defective within the warranty period stated above. New-Tronics Antenna Corp. does not assume nor is any person authorized to assume for it, any obligations other than that herein stated.

Any implied warranties, including but not limited to fitness for a particular purpose, is limited in duration for the above one year period. New-Tronics Antenna Corp. shall not be liable under this warranty, or any implied warranty, for loss of use of the product or for other consequential loss or damage incurred by the purchaser. Some states do not allow the exclusion or limitation of implied warranties of consequential damages and so the above exclusions or limitations may not apply in those states. This warranty gives you special legal rights and you may have other rights that vary from state to state.

This PDF courtesy of





This PDF courtesy of

